



MEACO 60L ROTA MOULDED Building Dryer



MEACO 60L ROTA MOULDED BUILDING DRYER

Introducing the new Meaco 60L Rota-Moulded Building Dryer with some unique Meaco twists. There are several rota-moulded building dryers on the world market and we looked carefully at what customers had to say and took the best bits from all of the user feedback before we designed and built the Meaco 60L.

Key Features of the Meaco 60L Building Dryer

- ✓ Unique Rota-Moulded design with simple rotary controls
- ✓ 60 litres per day at 30°C and 80%rh
- ✓ 35 litres per day at 26.7°C and 60%rh
- ✓ Stackable to save on storage space
- ✓ Only 705mm high
- ✓ Two year warranty

We are using a higher grade of components than is standard having strengthened the axle, metal connectors for the hose, rotary controls to simplify the control panel, a non-resettable hour counter, built in water pump and fold away handles. When you compare the overall specification of the Meaco 60L with other building dryers it makes a very attractive option with a spec that is hard to beat.

Why the Meaco 60L is the right building dryer for you

- ✓ Rota-moulding provides extra durability for the dehumidifier
- ✓ Preserves the look of the dehumidifier for longer
- ✓ Reinforced axial for extra strength
- ✓ Unique rotary control controls, very simple to use
- ✓ Metal hose connector
- ✓ Fold down handles
- ✓ Non-resettable hour counter
- ✓ Ductable - 5 metre maximum run
- ✓ Automatic defrost system
- ✓ Meaco Control Logic built in
- ✓ Stackable two high
- ✓ Built in pump with 3 metre lift

The Meaco 60L Rota-Moulded Building Dryer can be used in a variety of applications to dry spaces out after a flood or fire, provide directed, ducted dry air for building restoration, product storage or commercial applications.

SPECIFICATIONS



Nominal Air Flow Rate	510 m³/h
Temperature Range	5°C - 35°C
Defrosting System	Hot Gas
Continuous Drainage Option	Built in pump
Hour Counter	Yes
Electronic Control	On/off rotary control only
Rated Current	3.5 A
Power Consumption	30°C - 80%rh 780W
Extraction Rate	60 litres/24h
Rated Current	3.3 A
Power Consumption	26.7°C - 60%rh 750W
Extraction Rate	35litres/24h
Pump	3m high lift
Air Filter	Yes - washable
Fan Speeds	One
Compressor	Rotary
Refrigerant	R410a/640g
Duct Diameter	170mm, 5m maximum
Dimensions	705mm x 455mm x 500mm
Weight	38kg



Washable filter



Simple rotary control and hour counter



Quick connect metal hose fitting



Fold down handles